



FITTING INSTRUCTIONS FOR BRG0029SS
BRANDED RADIATOR GUARD
FOR KAWASAKI NINJA ZX-10R/RR 2021-



PICTURE A

THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

**IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF
OUR DEALERS OR HAVE FITTED BY A QUALIFIED TECHNICIAN.**

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE
WAY OF MOUNTING TO THE BIKE.


IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,
THESE RUBBER WASHERS CAN BE THROWN AWAY.

DIGITAL COPIES OF THESE INSTRUCTIONS ARE AVAILABLE FROM:

WWW.RG-RACING.COM



<u>TOOLS REQUIRED</u>	<u>GENERAL TORQUE SETTINGS</u>
<ul style="list-style-type: none">• Allen key set to include 4 & 5mm A/F.<ul style="list-style-type: none">• 10mm spanner or socket.• Phillips and flat bladed driver.<ul style="list-style-type: none">• Cable cutters.	M4 BOLT = 8Nm M5 BOLT = 12Nm M6 BOLT = 15Nm M8 BOLT = 20Nm M10 BOLT = 40Nm M12 BOLT = 40Nm



COMPONENT DIAGRAM




LEGEND

ITEM NO.	DESCRIPTION	QTY
ITEM 1	BRANDED RADIATOR GUARD (BRG0029SS)	1
ITEM 2	SELF ADHESIVE FOAM x 100mm LONG	4
ITEM 3	2.5mm CABLE TIES	8



PICTURE 1




PICTURE 2




PICTURE 3




PICTURE 4




PICTURE 5



PICTURE 6




PICTURE 7




PICTURE 8




PICTURE 9



PICTURE 10




PICTURE 11




PICTURE 12



PICTURE 13



PICTURE 14



PICTURE 15



FITTING INSTRUCTIONS

Near side (left side as you sit on the motorcycle)


- Remove the three plastic rivets arrowed in **pictures 1 and 2**.
- Remove the five bolts arrowed in **pictures 3, 4, 5, 6 and 7**.
- Carefully remove the lower fairing.

Off side (right side as you sit on the motorcycle)

- Remove the five bolts arrowed in **pictures 9, 10, 11, 12 and 13**.
- Carefully remove the lower fairing.
- Loosen the bolt arrowed in **picture 14**.
- **Remove the two bolts arrowed in picture 15 and carefully move the brake line bracket to allow fitment of the guard.**
- To fit the radiator guard to the bike, first cut the self-adhesive foam strip provided (**item 2**) into 10mm wide pieces and stick them to the back of the radiator guard frame (**item 1**), so that they will sit between the radiator guard and the radiator as shown **below**.



- Offer the radiator guard into position slotting the upper mounting flanges between the radiator mounting brackets and tighten the bolt to secure in position.
- Use the supplied cable ties (**item 3**) to secure the guard into position ensuring to pass the cable ties around the upper radiator mounts through the radiator frame and not the cooling matrix as shown below.



- **Refit the brake line bracket as original.**
- Refit both fairings as original.

ISSUE 2 21/09/2021 (NSY)

R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
 Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.


R&G



**MONTAGEANLEITUNG FÜR BRG0029SS KÜHLERSCHUTZ
(GEBRANDET) FÜR KAWASAKI NINJA ZX-10R/RR 2021-**



ABBILDUNG A



ALLE KIT-TEILE SIND AUF DEN NACHFOLGENDEN SEITEN ABGEBILDET UND GEKENNZEICHNET.

DIE ABGEBILDETEN TEILE DIENEN LEDIGLICH ZUR ERKLÄRUNG.

ÜBERPRÜFEN SIE ZUERST, DASS ALLE TEILE VORHANDEN SIND.

LESEN SIE DIE MONTAGEANLEITUNG KOMPLETT DURCH, BEVOR SIE ANFANGEN.

WENN SIE BEI DER MONTAGE DIESES PRODUKTES UNSICHER SIND, BITTE EINEN UNSERER HÄNDLER KONTAKTIEREN ODER DAS KIT VON EINEM QUALIFIZIERTEN ZWEIRAD-MECHANIKER MONTIEREN LASSEN.

DIE VERPACKUNG DER TEILE STELLT NICHT DIE REIHENFOLGE DER MONTAGE DAR.

HINWEIS FÜR KITS MIT PLASTIKUNTERLEGSCHWEIBEN AN DEN SCHRAUBEN –
DIESE PLASTIK-UNTERLEGSCHWEIBEN WERDEN NICHT FÜR DEN EINBAU BENÖTIGT.

EINE DIGITALE VERSION DIESER MONTAGEANLEITUNG KANN AUF FOLGENDER SEITE HERUNTERGELADEN WERDEN:

WWW.RG-RACING.COM


R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



SIE BENÖTIGEN FOLGENDES WERKZEUG	ALLGEM. ANZUGSDREHMOMENTE
<ul style="list-style-type: none"> • Satz Inbusschlüssel inkl. 4 & 5mm A/F <ul style="list-style-type: none"> • 10mm Steckschlüssel oder Schraubenschlüssel • Schraubenzieher (Kreuzschlitz und flachen Schraubenzieher) <ul style="list-style-type: none"> • Seitenschneider 	<p>M4 SCHRAUBE = 8Nm M5 SCHRAUBE = 12Nm M6 SCHRAUBE = 15Nm M8 SCHRAUBE = 20Nm M10 SCHRAUBE = 40Nm M12 SCHRAUBE = 40Nm</p>

ZEICHNUNG - TEILE



LIEFERUMFANG

ARTIKEL NR.	BESCHREIBUNG	MENGE
ARTIKEL 1	(GEBRANDET) KÜHLERSCHUTZ (BRG0029SS)	1
ARTIKEL 2	SELBSTKLEBENDER SCHAUMSTOFF x 100mm LÄNGE	4
ARTIKEL 3	2,5mm KABELBINDER	8



ABBILDUNG 1




ABBILDUNG 2



ABBILDUNG 3



ABBILDUNG 4




ABBILDUNG 5




ABBILDUNG 6




ABBILDUNG 7




ABBILDUNG 8



ABBILDUNG 9



ABBILDUNG 10




ABBILDUNG 11




ABBILDUNG 12



ABBILDUNG 13




ABBILDUNG 14




ABBILDUNG 15



MONTAGEANLEITUNG

Linke Seite (in Fahrtrichtung)



- Entfernen Sie die drei Plastiknieten, die in den **Abbildungen 1 und 2** markiert sind.
- Entfernen Sie die fünf Schrauben, die in den **Abbildungen 3, 4, 5, 6 und 7** gekennzeichnet sind.
- Entfernen Sie vorsichtig die untere Verkleidung.

Rechte Seite (in Fahrtrichtung)

- Entfernen Sie die fünf Schrauben, die in den **Abbildungen 9, 10, 11, 12 und 13** gekennzeichnet sind.
- Entfernen Sie vorsichtig die untere Verkleidung.
- Lösen Sie die Schraube, die in **Abbildung 14** markiert ist.
- **Entfernen Sie die zwei Schrauben, die in **Abbildung 15** markiert sind, und die Bremsschlauchhalterung, um die Montage des Kühlerschutz zu ermöglichen.**
- Um den Kühlerschutz am Motorrad montieren zu können, schneiden Sie die mitgelieferten Schaumstoffstreifen (**Artikel 2**) in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens (**Artikel 1**), so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind wie in **unten abgebildet**.



- Den Kühlerschutz in Position bringen und die oberen Montageflansche zwischen die Montagehalterungen schieben. Danach die Schraube in Position befestigen.
- Benutzen Sie die Kabelbinder vom Kit (**Artikel 3**), um den Kühlerschutz in Position zu befestigen. Stellen Sie sicher, dass die Kabelbinder montiert werden wie unten abgebildet (durch den Kühlerrahmen gefädelt, nicht durch das Gitter des Kühlerschutz):





- **Montieren Sie die Bremsschlauchhalterung wie ursprünglich wieder.**
- Montieren Sie beide Verkleidungen wie ursprünglich wieder.

ISSUE 2 21/09/2021 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P - at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



NOTICE DE MONTAGE POUR BRG0029SS
GRILLE DE PROTECTION RADIATEUR
POUR KAWASAKI NINJA ZX-10R/RR 2021-



PHOTO A



CE KIT CONTIENT LES ARTICLES ILLUSTRES ET ETIQUETES SUR LA PAGE.

CERTAINES PARTIES PEUVENT ETRE PRESENTES UNIQUEMENT POUR LA CLARTE DES
INSTRUCTIONS.

NE PAS PROCEDER AU MONTAGE TANT QUE VOUS N'ETES PAS SUR QUE TOUTES LES PIECES
SOIENT PRESENTES.

VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.

**EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ
UN DE NOS REVENDEURS OU FAITES APPEL A UN TECHNICIEN
QUALIFIÉ.**

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLE NE REPRESENTE PAS
NECESSAIREMENT LA MANIERE DE LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISEES POUR MAINTENIR LES COMPOSANTS
SUR LES BOULONS, ELLES PEUVENT ETRE JETEES.

NOTICE DISPONIBLE AU TELECHARGEMENT SUR :
WWW.RG-RACING.COM



OUTILS REQUIS	VALEURS DE SERRAGE
<ul style="list-style-type: none"> • Clés Allen 4 & 5mm. • Clé à molette 10mm. • Tournevis cruciforme et plat. <ul style="list-style-type: none"> • Coupe câble. 	<p>M4 BOULON = 8Nm M5 BOULON = 12Nm M6 BOULON = 15Nm M8 BOULON = 20Nm M10 BOULON = 40Nm M12 BOULON = 40Nm</p>




SCHÉMA DES COMPOSANTS



LÉGENDE

ARTICLE NO.	DESCRIPTION	QTÉ
ARTICLE 1	GRILLE DE PROTECTION (BRG0029SS)	1
ARTICLE 2	MOUSSE AUTOCOLLANTE x 100mm DE LONG	4
ARTICLE 3	2.5mm COLLIERS DE SERRAGE	8



PHOTO 1





PHOTO 2



R&G



PHOTO 3

PHOTO 4



PHOTO 5




PHOTO 6




PHOTO 7




PHOTO 8



R&G






PHOTO 9




PHOTO 10



PHOTO 11



PHOTO 12




PHOTO 13




PHOTO 14





PHOTO 15





NOTICE DE MONTAGE

Côté gauche (lorsqu'on est assis sur la moto)



- Retirez les trois rivets en plastique fléchés sur les photos 1 et 2.
- Retirez les cinq boulons fléchés sur les photos 3, 4, 5, 6 et 7.
- Retirer avec précaution le carénage inférieur.

Côté droit (lorsqu'on est assis sur la moto)

- Retirez les cinq boulons fléchés sur les photos 9, 10, 11, 12 et 13.
- Retirer avec précaution le carénage inférieur.
- Desserrez le boulon fléché sur la photo 14.
- Retirez les deux boulons fléchés sur la photo 15 et déplacez avec précaution le support de conduite de frein pour permettre le montage de la protection.
- Pour monter la protection de radiateur sur la moto, découpez d'abord la bande de mousse autocollante fournie (article 2) en morceaux de 10 mm de large et collez-les à l'arrière du cadre de protection de radiateur (article 1), de manière à ce qu'elles se placent entre le radiateur garde et le radiateur comme indiqué ci-dessous.



- Mettez la protection du radiateur en place en insérant les brides de montage supérieures entre les supports de montage du radiateur et serrez le boulon pour le fixer en position.
- Utilisez les colliers de serrage fournis (article 3) pour fixer la protection en position en veillant à faire passer les colliers de serrage autour des supports de radiateur supérieurs à travers le cadre du radiateur et non la matrice de refroidissement comme indiqué ci-dessous.



R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Reposer le support de conduite de frein comme d'origine.
- Reposer les deux carénages comme d'origine.

ISSUE 2 21/09/2021 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P - at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com