



## **FITTING INSTRUCTIONS FOR DG0061PRO**



**THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.**

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

**PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.**

**IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS  
OR HAVE FITTED BY A QUALIFIED TECHNICIAN.**

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF  
MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,  
THESE RUBBER WASHERS CAN BE THROWN AWAY.




<b>TOOLS REQUIRED</b>	<b>GENERAL TORQUE SETTINGS</b>
<ul style="list-style-type: none"> <li data-bbox="323 361 647 395">• SET OF ALLEN KEYS</li> <li data-bbox="271 428 700 462">• SOCKET SET OR SPANNERS</li> <li data-bbox="382 496 589 530">• WRATCHET</li> </ul>	<ul style="list-style-type: none"> <li data-bbox="986 361 1219 395">M4 BOLT = 8Nm</li> <li data-bbox="978 406 1227 440">M5 BOLT = 12Nm</li> <li data-bbox="978 451 1227 485">M6 BOLT = 15Nm</li> <li data-bbox="978 496 1227 530">M8 BOLT = 20Nm</li> <li data-bbox="970 541 1235 574">M10 BOLT = 40Nm</li> <li data-bbox="970 586 1235 619">M12 BOLT = 40Nm</li> </ul>

### **LEGEND**

ITEM NO.	DESCRIPTION	QTY
ITEM 1	DOWNPIPE GRILL (DG0061)	1
ITEM 2	M6 x 25mm BOLT	1
ITEM 3	M6 WASHER	2
ITEM 4	M6 J-CLIP	1

### **FITTING PICTURES**

**PICTURE 1**



**PICTURE 2**





## FITTING INSTRUCTIONS

1. Remove the bolt at the bottom of the radiator circled in **Picture 1.** (Keep this bolt safe)
2. Remove the plastic push clip on the under tray as circled in **Picture 2.**
3. Slide the J-clip (**Item 4**) onto the bottom tab of the downpipe grill (**Item 1**)
4. Slide the Downpipe grill into place and tighten it to the bottom radiator bracket using the original bolt that was removed in step 1, and 1x of the M6 washers (**Item 3**). It may be necessary to remove one side of the fairing to do this, please refer to the manufacturer guidelines on how to do this.
5. Refit the fairing panel (if removed). Place the remaining M6 washer (**Item 3**) over the supplied M6 bolt (**Item 2**) and through the hole left by removing the plastic pop-clip in step 2 into the J-clip (**Item 4**).
6. Ensure the downpipe grill is aligned correctly before tightening.
7. Check all components are secure and all bolts are tight before riding.

ISSUE 2 – 09/01/2026 (MH)

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.


Racing Technique Ltd T/A R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



## **NOTICE DE MONTAGE POUR DG0061PRO**



### **CE KIT CONTIENT LES ARTICLES ILLUSTRES ET ETIQUETES SUR LA PAGE.**

CERTAINES PARTIES PEUVENT ETRE PRESENTES UNIQUEMENT POUR LA CLARTE DES INSTRUCTIONS.

NE PAS PROCEDER AU MONTAGE TANT QUE VOUS N'ETES PAS SUR QUE TOUTES LES PIECES SOIENT PRESENTES.

**VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.**

**EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ UN DE NOS REVENDEURS OU FAITES APPEL A UN TECHNICIEN QUALIFIÉ.**

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA MANIERE DE LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISEES POUR MAINTENIR LES COMPOSANTS SUR LES BOULONS, ELLES PEUVENT ETRE JETEES.

Racing Technique Ltd T/A R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



<b>OUTILS REQUIS</b>	<b>VALEURS DE SERRAGE</b>
• CLÉS ALLEN	M4 BOULON = 8Nm
• CLÉ À CLIQUET	M5 BOULON = 12Nm
• CLIQUET	M6 BOULON = 15Nm
	M8 BOULON = 20Nm
	M10 BOULON = 40Nm
	M12 BOULON = 40Nm

### **LÉGENDE**

<b>ARTICLE NO.</b>	<b>DESCRIPTION</b>	<b>QTÉ</b>
ARTICLE 1	GRILLE DE COLLECTEURS (DG0061)	1
ARTICLE 2	M6 x 25mm BOULON	1
ARTICLE 3	M6 RONDELLE	2
ARTICLE 4	M6 J-CLIP	1

### **PHOTOS DE MONTAGE**

PHOTO 1




PHOTO 2





## **NOTICE DE MONTAGE**

8. Retirez le boulon situé en bas du radiateur, entouré sur la photo 1 (Conservez ce boulon en lieu sûr).
9. Retirez le clip de fixation en plastique situé sur le cache inférieur, entouré sur la photo 2.
10. Glissez le clip en J (article 4) sur la languette inférieure de la grille du tuyau d'échappement (article 1).
11. Glissez la grille du tuyau d'échappement en place et fixez-la au support inférieur du radiateur à l'aide du boulon d'origine retiré à l'étape 1 et d'une rondelle M6 (article 3). Il peut être nécessaire de retirer un côté du carénage pour ce faire ; veuillez vous référer aux instructions du fabricant.
12. Remontez le carénage (s'il a été retiré). Placez la rondelle M6 restante (article 3) sur le boulon M6 fourni (article 2) et insérez-la dans le clip en J (article 4) à travers l'orifice laissé par le clip de fixation en plastique retiré à l'étape 2.
13. Assurez-vous que la grille du tuyau d'échappement soit correctement alignée avant de la serrer.
14. Vérifiez que tous les composants soient bien fixés et que tous les boulons soient bien serrés avant de rouler.

ISSUE 2 – 09/01/2026 (MH)

### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Racing Technique Ltd T/A R&G

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)