

FITTING INSTRUCTIONS FOR FP0162BK FORK PROTECTORS YAMAHA YZF-R25 2014-






THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW. DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with a plastic tube separating components on the spindle bar (this tube should be discarded).

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



LEFT HAND SIDE

RIGHT HAND SIDE



TOOLS REQUIRED

• Socket set to include 2x 10mm sockets

FITTING INSTRUCTIONS

- Place the spindle-bar (SB0115) through the front spindle from the left hand side (ensure the longer reduced diameter end goes in first).
- Place the spacer with the larger bore size (S0843) over the exposed spindle bar on the right hand side (as shown above).
- Place either crash protector (B0445M) over the exposed spindle bar on the right hand side (as shown above).
- Place one of the washers onto the spindle.
- Engage one of the nyloc nuts onto the spindle (please ensure the nut is fully engaged).
- Place the remaining spacer with the smaller bore size (S0842) over the exposed spindle bar on the left hand side (as shown above).
- Place the remaining crash protector (B0445M) over the exposed spindle bar on the left hand side (as shown above).
- Place the remaining washer onto the spindle.
- Engage the remaining nyloc nut onto the spindle (please ensure the nut is fully engaged).
- Tighten both nuts so equal amounts protrude from either side (please ensure the logo is located at the top and bottom of the crash protector). Do not overtighten the nyloc nuts will hold it tight.

ISSUE 1 13/11/2014 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



INSTRUCTIONS DE MONTAGE POUR FP0162BK Protections Fourche YAMAHA YZF-R25 2014-






LE KIT CONTIENT LES ARTICLES EXPOSES CI-DESSOUS, VERIFIER QUE TOUTES LES PIECES SOIENT PRESENTES AVANT DE PROCEDER AU MONTAGE.

<u>LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.</u>

Notez que si les kits sont emballés avec un tube en plastic qui sépare les composants sur l'axe, ce tube doit être jeté.

LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT)





OUTILS REQUIS

• Jeu de clés 2x 10mm

INSTRUCTIONS DE MONTAGE

- Placer l'axe (SB0115) dans le moyeu du coté gauche (Veiller à ce que le diamètre réduit passe en 1er).
- Placer l'entretoise avec le l'entretoise à l'alésage le plus large (S0843) sur l'extrémité de l'axe du coté droit (voir ci dessus).
- Placer la protection crash (B0445M) sur l'extrémité de l'axe du coté droit (voir ci dessus).
- Placer une des rondelles sur l'axe.
- Engager un des écrous sur l'axe (Veiller à ce que l'écrou soit complètement engagé).
- Placer l'entretoise restante avec l'alésage le plus court (S0842) sur l'extrémité de l'axe du coté gauche (voir ci dessus).
- Placer la protection crash restante (B0445M) sur l'extrémité de l'axe du coté gauche (voir ci dessus).
- Place la rondelle restante sur l'axe.
- Engager l'écrou restant sur l'axe (Veiller à ce que l'écrou soit complètement engagé).
- Serrer les deux écrous de façon à ce que les longueurs dépassantes de chaque coté soient égales (Veiller à ce que le logo soit placé sur le haut et au bas de la protection crash). Ne pas bloquer – les écrous fixent l'ensemble.

ISSUE 1 13/11/2014 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

