



Fitting Instructions for RAD0129BK Radiator Guard
MV AGUSTA F3 2012



In This Kit There Should Be
1x Radiator Guard (RAD0129BK)
2x 100mm Lengths of self-adhesive Foam
1x Cable Tie



Picture 1



Picture 2



Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8

TOOLS REQUIRED

- Socket set to include 8mm socket & wrench.
- Set of metric Allen keys to include 4mm A/F sizes.



FITTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove both side fairings from the bike.
- Remove the bolt that secures the top of the radiator to the frame, on the left side of the bike, as shown in picture 1.
- Remove the bolt that secures the radiator to the oil radiator. This is located at the bottom of the radiator on the right side of the bike, as shown in picture 2.
- The oil radiator can now be pulled away from the main radiator, as shown in picture 3.
- To remove the radiator from its mounting lug on the right side of the bike, ensure the left side mount is clear and gently slide the radiator off the frame mount, as shown in picture 4.
- Offer the R&G Radiator Guard into position and locate the upper tab on the right side over the frame mount, before sliding the radiator back on, as shown in picture 5.
- The upper tab on the left side should now locate in position, as shown in picture 6. Refit the original bolt and loosely tighten.
- Position the oil radiator and radiator guard tab in place, as shown in picture 7. Refit the original bolt and loosely tighten.
- On the bottom of the right side, there is a small tab to feed the cable tie through. Position the cable tie through this and around the radiator mounting bracket, as shown in picture 8, before tightening.
- Ensure all bolts are tightened securely and the radiator is correctly mounted.
- Refit both side fairings.

ISSUE 1 23/07/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage
RAD0129BK Grille de protection radiateur
MV AGUSTA F3 2012



Le kit doit contenir:
1x Grille radiateur (RAD0129BK)
2x 100mm Longueur de mousse autocollante
1x Attache câble



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Photo 7



Photo 8

Outils requis

- Clé de 8mm
- Clé Allen 4mm



Instructions de montage

- Pour installer la grille de protection sur la moto, couper la mousse en bandeaux de 10mm, puis collez là au bas du cadre de sorte à ce que ces bandeaux se retrouvent entre le cadre de la moto et la grille de protection R&G.
- Enlever le carénage de la moto des 2 cotés.
- Enlever le boulon qui fixe le haut du radiateur au cadre (photo 1).
- Enlever le boulon qui fixe le radiateur au radiateur d'huile, logé au bas du radiateur, du coté droit de la moto (Photo 2).
- Le radiateur d'huile peut à présent être tire du radiateur principal (Photo 3).
- Pour enlever le radiateur de son support de fixation du coté droit de la moto, assurez vous que le support du coté gauche soit libre puis glisser le radiateur en dehors du support de cadre (photo 4).
- Mettre la grille de protection radiateur en position puis loger la languette supérieure du coté droit autour du support de cadre, avant de re-glisser le radiateur (Photo 5).
- La languette supérieure du coté gauche devrait à présent se mettre en position (Photo 6). Remettre le boulon d'origine et serrer (légèrement).
- Positionner le radiateur d'huile en place (photo 7). Remettre le boulon d'origine et serrer (légèrement).
- En bas à droit, il y a une petite languette pour passer l'attache câble à travers. Positionner l'attache câble à travers et autour du support de fixation du radiateur (photo 8), avant de serrer.
- S'assurer que tous les boulons soient correctement serrés et que le radiateur soit correctement monté.
- Remettre le carénage des 2 cotés.

ISSUE 1 23/07/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Montageanleitung für den RAD0129BK Kühlerschutz
MV AGUSTA F3 Modell 2012



Dieser Kit beinhaltet:
1x Kühlerschutz (RAD0129BK)
2x 100mm selbstklebende Schaumstoffstreifen
1x Kabelbinder



Abbildung 1



Abbildung 2



Abbildung 3



Abbildung 4



Abbildung 5



Abbildung 6



Abbildung 7



Abbildung 8

SIE BENÖTIGEN FOLGENDES WERKZEUG:

- 8 mm Steckschlüssel
- Satz Inbusschlüssel inkl. 4 mm Größe A/F



MONTAGEANLEITUNG

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoff-Streifen in 10 mm breiten Streifen und kleben Sie die auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie beide Seitenverkleidungen vom Motorrad.
- Entfernen Sie die Schraube, die den Kühler oben am Rahmen befestigt (auf der linken Seite des Motorrades – siehe Abbildung 1).
- Entfernen Sie die Schrauben, die den Kühler mit dem Ölluftkühler befestigt. Diese Schraube ist unten auf dem Kühler, auf der rechten Seite des Motorrades, wie in Abbildung 2 abgebildet.
- Den Ölluftkühler nun vorsichtig vom Hauptkühler entfernen - siehe Abbildung 3.
- Um den Kühler von der Montagelasche auf der rechten Seite des Motorrades zu entfernen, stellen Sie zuerst sicher, dass die Halterung auf der linken Seite frei ist, dann vorsichtig den Kühler von der Rahmenhalterung entfernen – siehe Abbildung 4.
- Den R&G Kühlerschutz in Position bringen und die obere Lasche auf der rechten Seite über den Rahmenhalter fixieren, bevor Sie den Kühler wieder anbringen – siehe Abbildung 5.
- Die obere Lasche auf der linken Seite nun in Position fixieren, wie in Abbildung 6 abgebildet. Montieren Sie die Originalschraube wieder, aber noch nicht festziehen.
- Den Ölluftkühler und den Kühlerschutz in Position anbringen – siehe Abbildung 7. Montieren Sie die Originalschraube wieder aber nicht noch nicht festziehen.
- Unten auf der rechten Seite ist eine kleine Öse, durch sie Sie den Kabelbinder führen können. Den Kabelbinder durch die Öse führen, dann um die Halterung für den Kühler wickeln, wie in Abbildung 8 abgebildet. Ziehen Sie dann den Kabelbinder fest.
- Nun alle Schrauben festziehen und überprüfen, dass der Kühler ordnungsgemäß montiert ist.
- Montieren Sie beide Seitenverkleidungen wieder.

AUSGABE 1 23/07/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com