



Fitting Instructions for SRG0008 Radiator Guard
KTM 1190 ADVENTURE 2013



In This Kit There Should Be
1x Radiator Guard (SRG0008)
2x M5 x 16mm Long Button Head Bolts
2x M5 Washers
2x S0637 Spacers (4.5mm long)
2x Cable Tie
2x 100mm Lengths of self-adhesive Foam



Picture 1



Picture 2



Picture 3



Picture 4

TOOLS REQUIRED

- T20 Torx socket and wrench.
- 3mm A/F allen key.
- Cable cutters.

FITTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the two Torx bolts that secure the radiator surround plastic in place on either side of the radiator, as shown in picture 1.
- Take the R&G Radiator Guard and locate one washer over one M5 x 16mm long button head bolt. Now insert this through one of the mounting holes on the radiator guard, before fitting one spacer onto the exposed end of the thread (larger diameter first), as shown in picture 2. Repeat this for the mounting hole on the other side of the radiator guard.
- Ensure these spacers remain in position and offer the R&G Radiator Guard into position. This will need to be gently slid up to ensure the top brackets fit behind the plastic.
- The bolts and spacer will now align with the mounting holes on the plastic. Locate the bolts and spacers, before tightening, as shown in picture 3.
- With the upper mounts sitting behind the plastic, insert one cable tie on each side and loop around the radiator mount and then tighten, as shown in picture 4.
- Ensure all bolts are tightened evenly and the radiator is correctly mounted.

ISSUE 1 26/06/2013 (AR)

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage RAD0148BK Grille de protection radiateur
KTM 1190 ADVENTURE 2013



Le kit doit contenir:

- 1 x Grille de protection radiateur (SRG0008)
- 2x M5 x 16mm Boulons
- 2x M5 Rondelles
- 2x S0637 Entretoises (4.5mm de long)
- 2x Attache câble
- 2x 100mm Mousse autocollante



Photo 1



Photo 2



Photo 3



Photo 4

Outils requis

- Clé Torx T20.
- Clé Allen 3mm.
- Coupe câble
- .

Instructions de montage

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever les 2 boulons Torx qui fixent le contour de radiateur en plastique en place d'un coté du radiateur (Photo 1).
- Prendre la grille de protection R&G et insérer une rondelle autour du boulon M5 x 16mm. A présent, insérer le à travers un des trous de fixation sur la grille de protection, avant d'insérer une entretoise sur l'extrémité du filetage (le diamètre le plus large en 1er), (Photo 2). Répéter cela pour le trou de fixation de l'autre coté de la grille de protection.
- Assurez vous que ces entretoises soient bien en position et placer la grille de protection R&G en position. Elle devra être glissée pour être sûr que les supports soient placés derrière le plastique.
- Les boulons et l'entretoise doivent à présent être alignés avec les trous de fixation sur le plastique. Placer les boulon et entretoises, avant de serrer (Photo 3).
- Avec les supports supérieurs placés derrière le plastique, insérer un serre câble de chaque coté et entourer le support de radiateur puis serrer (Photo 4).

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Assurez vous que tous les boulons soient serrés de façon égale et que le radiateur soit correctement monté.

ISSUE 1 26/06/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



Montageanleitung für den SRG0008 Kühlerschutz
KTM 1190 ADVENTURE 2013



Dieser Kit beinhaltet:

- 1x Kühlerschutz (SRG0008)**
- 2x M5 x 16mm Halbrundkopfschrauben**
- 2x M5 Unterlegscheiben**
- 2x S0637 Abstandshalter (4,5mm Länge)**
- 2 x Kabelbinder**
- 2x 100mm selbstklebende Schaumstoffstreifen**



Abbildung 1



Abbildung 2



Abbildung 3



Abbildung 4

SIE BENÖTIGEN FOLGENDES WERKZEUG:

- T25 Torx-Schlüssel
- 3mm Inbusschlüssel
- Seitenschneider

MONTAGEANLEITUNG

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoff-Streifen in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie die zwei Torx-Schrauben, die die Verkleidung an beiden Seiten des Kühlers befestigen – siehe Abbildung 1.
- Nehmen Sie den R&G Kühlerschutz, eine M5 x 16mm Halbrundkopfschraube und eine Unterlegscheibe. Schieben Sie die Unterlegscheibe zum Schraubenkopf hoch und führen Sie die Schraube in eine der Öffnungen oben am Kühlerschutz ein. Das hervorstehende Gewinde mit einem Abstandshalter versehen (großer Durchmesser zuerst) wie in Abbildung 2 dargestellt. Diesen Schritt auf der anderen Seite des Kühlerschutzes wiederholen.
- Bitte darauf achten, dass die Abstandshalter in Position bleiben und montieren Sie den R&G Kühlerschutz, der leicht nach oben geschoben werden muss, sodass die oberen Halterungen hinter dem Plastik reinpassen.



- Die Schrauben und Abstandshalter werden jetzt mit den Montageöffnungen auf dem Plastik bündig sein. Ziehen Sie die Schrauben fest – siehe Abbildung 3.
- Die oberen Halterungen sind jetzt hinter dem Plastik – einen Kabelbinder an jeder Seite anbringen, um die Kühlerhalterung wickeln und festziehen – wie in Abbildung 4.
- Überprüfen Sie, dass der Kühlerschutz richtig montiert ist und die Schrauben gleichmäßig festgezogen sind.

AUSGABE 1 26/06/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.