

FITTING INSTRUCTIONS FOR CP0202BL/WH LOWER CRASH PROTECTORS YAMAHA YZF R6 '06 ONWARDS



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

- Take the R&G bar and slide it through the swing arm pivot bolt.
- On the RHS take the longer aluminium spacer and slide it over the bar (small diameter towards the bike) and locate into the hexagonal shaped end of the pivot bolt. Take one of the protectors and slide over the bar followed by one of the 10mm washers then one of the nyloc nuts.
- On the LHS slide the shorter spacer on to the bar and up to the end of the pivot bolt (so smaller spigot locates into spindle), followed by the protector, washer and nyloc nut. Please note the thin sectioned counter bore on inboard side of bobbin is cosmetic only and does not have any bearing on strength or operation of bobbin.
- With a socket on either end of the bar, tighten the assembly. DO NOT TIGHTEN ABOVE 40nm as you will strip the threads on the bar/nut
- When the assembly is tight push the end caps into both protectors.
- PLEASE NOTE BOBBIN MUST BE POSITIONED HORIZONTALY AS SHOW ABOVE

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.